A Logic Agent That Speaks Spanish: Prolog Behind an A2A Protocol, Meta-interpreters, and Context as Program

David Ragel
dragel@us.es

Abstract

This article explains, in plain language, how a small logic program written in Prolog —an electrical circuit with lights, switches and fuses that can say which lights are on and why— was wrapped inside an agent that converses in Spanish with other agents through the A2A protocol. The client describes its circuit in its own words; the agent interviews it, assembles the circuit as Prolog facts, and answers what is lit, why it is lit and why it is not. The division of roles is strict: a large language model (LLM) only translates and phrases, while a validator written as ordinary code and the Prolog core decide what is valid and what is true. In three real conversations with a client that is itself a language model, the loaded circuit matched the ground truth of the scenario and all nineteen answers matched an independent simulator; eight attacks written in natural language failed to execute anything. In a second part, the same idea is applied to an agent that installs programs on a computer: a small logic base, a single predicate, and several tiny meta-interpreters that traverse it to verify, plan, install and learn. When a piece of knowledge is missing, a meta-interpreter builds the context and wakes up a language model to write the missing program fragment. An experiment with twenty-one tasks and nine context variants shows that the decisive piece is the *signature* of the requested program. The new core takes 1230 lines versus 6049 for the previous version. The observed failures and the limits are discussed frankly: few conversations and a single type of client, a sample and not a statistic.

Contents

1 Introduction **4**

2 Background Concepts **5**

2.1 Agents and Language Models 5

2.2 The A2A Protocol 5

2.3 Prolog and the Reasoner 5

2.4 Meta-interpreters 6

3 The Starting Point: A Circuit in Prolog **6**

4 The Electrical Agent **7**

4.1 The Idea: Spanish on the Outside, Prolog on the Inside 7

4.2 The Card . . . 7
4.3 The Chain: From What You Say to Prolog, and Back . . . 8
4.4 Who Decides What . . . 9
4.5 The JSON Is Internal . . . 10

5 The Interview and the Teaching 10
5.1 Not Filling Gaps: Asking . . . 10
5.2 How a Circuit Is Told . . . 10
5.3 Three Client Styles, Three Interviews . . . 11
5.4 Teaching Someone Who Does Not Know How to Describe . . . 11

6 The Questions It Can Answer 12
6.1 What Is Lit . . . 12
6.2 What Makes a Light Be Lit . . . 12
6.3 Why It Is Not Lit: the "Or" and the "And" . . . 12
6.4 Why It Changed . . . 13
6.5 How It Is Lit: Asking for an Explanation . . . 13

7 Inside: Tasks, Observation and Limits 14
7.1 The Life Cycle of a Task, Turn by Turn . . . 14
7.2 Who Watches Without Touching . . . 14
7.3 Limits and What Is Denied . . . 14

8 How the Electrical Agent Was Evaluated 15

9 Results of the Electrical Agent 16
9.1 A Real Conversation, Step by Step: the Workshop . . . 16
9.2 Another Complete Conversation: the Garage . . . 16
9.3 The Figures of the Three Conversations . . . 17
9.4 Where the Time Goes . . . 18
9.5 The Validator and the Check of the Phrasing . . . 18
9.6 Security: Eight Attacks in Natural Language . . . 18
9.7 Automated Checks . . . 18
9.8 Observed Failures . . . 19

10 Second Part: An Agent That Installs and Learns 20
10.1 The Client Says What It Wants; the Rest Stays Inside . . . 20
10.2 A Logic Base and a Single Predicate . . . 20

10.3 Several Small Meta-interpreters over the Same Logic 21

11 Context as Program **22**

11.1 A Gap in the Base 22

11.2 Asking Is Waking Up an LLM; the Human, Only at the End 24

12 Which Pieces of the Context Matter: An Experiment **24**

12.1 Design 24

12.2 Results 25

12.3 The Errors Change Nature 26

13 A Real Test on a Computer **26**

14 How Much Was Simplified and What Was Tested **28**

14.1 The Simplicity Measure 28

14.2 What Was Tested 28

14.3 What Was Real and What Was Simulated 29

15 Discussion **29**

15.1 What Works and Why 29

15.2 Limits 29

15.3 What Remains to Be Built 30

16 Conclusion **30**

Glossary **31**

References **32**

1 Introduction

Imagine you have a simple electrical installation at home: a socket, a power strip, a desk lamp with its switch and a fluorescent tube with its fuse. One day the lamp does not light up and you want to know why. You could ask an electrician friend, telling him in your own words: "I have the plug in, I switched the switch off, why doesn't the lamp light?". Your friend does not need you to draw a diagram with standardized symbols; he asks you a couple of questions if something does not add up, and then he explains it to you.[1]

The work described here tries to build something similar, but between programs. There is an "electrician" that is a logic program written in Prolog: it knows the rules of how current flows through wires, switches and fuses, and it is able to prove which lights are on and to explain why. That program already existed as a teaching example. What was missing was a way for other programs —specifically, other agents based on language models— to talk to it without knowing Prolog, without knowing any format and without seeing its internals. The solution is to wrap it in an *agent* that communicates through the A2A protocol and that, on the outside, speaks only Spanish.

The underlying tension is well known. Large language models understand very well what a person says in their own words, but they can make mistakes, make things up or be talked into something by a malicious text. Logic programs, on the other hand, do not make things up: they either prove a conclusion from the facts or they do not, and they can show the complete reasoning. The bet of this work is to combine the two with a very strict division of roles: the language model only *translates* what the client says into a draft of fixed form and *phrases* the final answer; everything else —deciding what is valid, what is true, what gets assembled and what gets answered— is decided by ordinary code and the logical reasoner. Throughout the article we will use colors, just like the figures: in *orange*, what the language model does, which may be wrong; in *green*, what the code and Prolog do, which decide.

The article has two parts. The first (Sections 3 to 9) presents the *electrical agent*: how it interviews the client, how it translates the client's description, which questions it can answer, how it protects itself and what was measured in three real conversations. The second (Sections 10 to 14) goes one step further: it applies the same philosophy to an agent that installs programs on a real computer and that, when it lacks a piece of knowledge, learns it. Two ideas appear there that are the heart of the work: that a handful of small *meta-interpreters* can traverse a single logic to do different things, and that what is really programmed, when a language model is used, is the *context* given to it. The discussion (Section 15) frankly gathers the failures and limits, and the conclusion summarizes what was learned. At the end there is a short glossary.

The reader is not assumed to know Prolog or what an agent is. For that reason Section 2 explains, before using them, the five concepts that appear again and again: agent, language model, A2A protocol, reasoner and meta-interpreter.

[1] The conversations quoted in this article were held in Spanish with the agent described; they are translated here into English.

2 Background Concepts

2.1 Agents and Language Models

In this article, an *agent* is a program that receives messages, does something with them and replies, with some autonomy to decide how to do so. Many current agents are built around a *language model* (LLM, for large language model): a program trained on enormous amounts of text that, given an input text, produces a plausible output text. A language model is very good at understanding sentences such as "I turn the plug off, I turn s1 on, I mean I raise it", but it does not guarantee that what it writes is true. That is the reason why, in this work, it is never given the last word.

Several specific language models appear by name in the experiments: *sonnet*, *opus* and *haiku* (which act as translators or as authors of small programs) and *gemma*, a small model that the installer agent installs on a computer. Here it is enough to know that some are more capable than others: the course treats opus as "the strongest" and haiku as a more modest one.

2.2 The A2A Protocol

When two agents want to talk to each other they need to agree on *how*: where each one is located, how it introduces itself, how a message is sent and how to know the state of a request. A2A (for *agent to agent*) is a protocol that fixes those rules. For our purposes, it has three ingredients:

- The **agent card**: a small document that the agent publishes at a known address and that says who it is, what it is for, which skills it offers and which kinds of messages it accepts. It is the only thing the other agent needs to read in order to start talking to it. In our case it is published at the path `/.well-known/agent-card.json`.
- The **skills**: each with its name, its description, some tags and some examples. They are the "menu" of what the agent knows how to do.
- The **tasks**: each message that a client sends gives rise to a task, which goes through states —submitted, working, input required, completed or failed— until it finishes. The client groups its tasks into a conversation by means of an identifier.

What matters about the protocol is that it cleanly separates the outside from the inside: the other agent sees the card and the replies, and nothing else. Whatever is inside —in our case, a language model, a validator and a Prolog program— stays hidden.

2.3 Prolog and the Reasoner

Prolog is a logic programming language. Instead of writing a sequence of instructions, one writes *facts* (things that are true) and *rules* (how some truths are deduced from others), and then one makes *queries*. A toy example, in the spirit of the circuit, would be:

```
tiene_corriente(entrada).
```

```
conectado(c1, entrada).
tiene_corriente(X) :- conectado(X, Y), tiene_corriente(Y).
```

(The identifiers are in Spanish, as in the system: `tiene_corriente` means "has current" and `conectado` means "connected".) The first two lines are facts: the input has current and the wire `c1` is connected to the input. The third is a rule: something has current if it is connected to something else that has current. If one queries `tiene_corriente(c1)`, Prolog chains the rule with the facts and answers yes. (This fragment is only an illustration of the style; it is not the code of the system.)

We call *reasoner* the program that, from facts and rules, deduces conclusions. In the electrical agent, the reasoner is what the course calls the *Prolog core*: the original electrical example, with its rules about lights, wires, switches and fuses. What is valuable about such a reasoner is that it does not make things up: every conclusion has behind it a *proof*, that is, the chain of facts and rules that supports it. That proof can be represented as a *tree*: at the root is the conclusion ("the lamp is lit"), and each branch goes down toward the reasons ("it is a light", "it is in good condition", "current reaches it") until reaching the leaves, which are facts.

2.4 Meta-interpreters

Normally, Prolog runs a program on its own: you give it a query and it searches for the proof. A *meta-interpreter* is a small Prolog program that runs another Prolog program *by hand*, step by step, and that for that very reason can do something more in the meantime: record the proof tree, stop to ask a question, count the steps, execute actions at certain leaves or note where the proof fails. The most classical form, which appears in textbooks, fits in three clauses and returns the proof tree of a goal:

```
prueba(true, true) :- !.
prueba((A,B), (PA,PB)) :- !, prueba(A, PA), prueba(B, PB).
prueba(H, (H :- P)) :- clause(H, Cuerpo), prueba(Cuerpo, P).
```

(Here `prueba` means "proof" and `Cuerpo` means "body".) It reads as follows: proving `true` costs nothing; proving two goals in a row is proving one and then the other; and proving any other goal is searching for a rule whose head matches and proving its body, recording the result. (We show it as an illustration of the idea; the course says that the tree meta-interpreter it uses, inherited from Topic 6 of the university subject, has three clauses, but it does not reproduce its text.)

The beauty of meta-interpreters is that they are *small* and *specialized*: each one can do a single thing over the same logic. That idea will be central in the second part of the article.

3 The Starting Point: A Circuit in Prolog

The starting electrical example is a circuit written in Prolog with lights, switches and circuit breakers (fuses), which can say which lights are on and why. The key piece of its design is *time*. Everything that happens in the circuit —assembling it, raising a switch, unplugging a plug, a bulb burning out— is an *event* with its number. Thus, every Prolog fact carries the number

of the event that created it: a switch is not simply "up", but "up since event one". This makes it possible to ask about the state of the circuit at a specific *moment* and, above all, to answer which happening was responsible for a situation.

In practice, the agent keeps a map between the happenings as the client tells them and the internal moments of the core. For example, in one of the test scenarios (the workshop), the assembly corresponds to moment seventeen and happening three to moment twenty. The client never sees those internal numbers; it sees "the assembly" and "happening three".

The vocabulary of the circuit is deliberately closed: current inputs, wires, lights, switches, changeover switches (which send the current to one wire when they are up and to another when they are down), plugs and sockets, and fuses. Each wire can carry a *condition*: it conducts only if a certain switch is up, for example. A plug, in this model, is the same as a switch: plugged in it acts as "up" and unplugged as "down"; the happenings "plug in" and "unplug" are understood as raising and lowering. Whatever cannot be expressed with these pieces —a timer, a relay— is left out, and the agent does not invent it.

The original example also had two *aspects*, two observers that watch what happens without changing it. The *Log* (Registro) records, numbered, everything that happens in the circuit. The *Reflection* (Reflexión) does the same and additionally asks the logic and contrasts what the objects say with what the Prolog says. As will be seen in Section 7, in the conversational agent these aspects are not hooked up: their equivalents are the event numbers of the assembly and the comparison with a simulator during the tests.

4 The Electrical Agent

4.1 The Idea: Spanish on the Outside, Prolog on the Inside

The idea is to encapsulate the circuit in an agent that speaks Spanish. On the outside, it is one more agent of the A2A protocol, with which another agent converses in natural language. On the inside is the Prolog, which nobody sees. Other agents tell it their circuit in their own words; the agent —which we will call the *logic agent*— interviews them, assembles the circuit and answers the same questions that the example already answered: what is lit, why it is lit and why it is not.

Neither the Prolog, nor its rules, nor its memory are exposed. The agent offers a main skill, *conversing*, which speaks Spanish. And, only for automated tests, four shortcuts in a structured data format (JSON). That JSON is internal: normally it is written by the logic agent itself when translating what it hears, as explained below.

4.2 The Card

The agent's card says who it is —the electrical agent, version 0.2— and what it is for: it speaks Spanish, interviews the client about its circuit, assembles it and explains its conclusions. It advertises five skills. The main one is conversing, in natural language. The other four are the JSON shortcuts, intended only for automated tests and not for clients: defining an architecture, asking, explaining and teaching. Each skill has its name, its description, its tags and its examples.

The card also declares what the agent does *not* do: it does not emit streaming replies as




Figure 1: The complete chain of a message: what the client says (blue) is translated into a JSON draft (orange, language model), goes through the validator, is assembled as Prolog facts and is solved by the core (green, code and logic). Only at the end does the language model intervene again to phrase the sentence, which the code checks before sending it: every piece, moment or happening cited must be in the output of the core and there must be no Prolog notation. If the phrasing fails twice, a deterministic phrasing is used. (The quoted sentence is the English rendering of the original Spanish; `lampara_mesa` is the system's identifier for the desk lamp.)

they are generated, nor does it notify an external address when it finishes (what in jargon is called a *webhook*). And it declares what it does do: it keeps the state history of each task. It accepts text and JSON, and answers with text and JSON.

The card is the only thing the other agent sees. The server publishes it at the path `/.well-known/agent-card.json`, by default on port 8923 of the machine itself, and it listens only there; the test conversations were held on port 8925.

4.3 The Chain: From What You Say to Prolog, and Back

The journey of a client message has six stages, which Figure 1 summarizes in its top strip.

1. What you say. The client writes in free text: “the plug is in”, “I turn the plug off”, “I turn s1 on, I mean I raise it”, “why doesn't the lamp light?”. Nobody has asked it for JSON, or Prolog, or piece names.

2. The draft (orange). The language model translates that sentence into a draft of fixed form: pieces, wires with their condition, happenings, or else a question. It never writes Prolog.

It is the only thing it does in this stretch, and that is why it is painted orange: it can be wrong. In a real example, from a client's sentence, the translator wrote a JSON with four pieces, a wire that only conducts if `s1` is up and one happening, "raise s1"; it also noted a doubt of its own, which later became a question to the client in Spanish.

3. The validator (green). The draft *always* goes through the validator, which is ordinary code and does not trust the model. It checks that the names are valid, that the piece types belong to a closed list, that the conditions also belong to a closed list, that the wires join pieces that exist and that there are no loops. What does not fit does not get in. Afterwards, the composite types, such as the plug, are expanded into the pieces that the core already knows.

4. The Prolog facts (green). The validated circuit is assembled as Prolog facts, each with its event number, and the number is stored in the map of moments we discussed earlier.

5. The core (green). The questions are also translated: "why doesn't the desk lamp light, at the assembly". But the Prolog query is not written by the language model: the agent itself builds it with the already validated data. The core answers with the truth. In the example of the figure, the lamp does not receive current because it has only one route, and on that route there is a break: `s1` would have to be up, and event nine left it down. No language model intervened in this conclusion.

6. The sentence (orange, checked in green). Only at the end does the language model speak again, to phrase the answer in Spanish from what the core said. In the example of Figure 1, the phrasing took 8.5 seconds and said: "The desk lamp is not lit in the initial state because no current reaches it. [...] That path is cut because s1 has been down since the assembly, and for current to flow s1 would have to be up". Before sending it, the code checks that all the pieces, moments and happenings it cites exist in the output of the core and that there is no Prolog notation. If the phrasing fails twice, the agent delivers a *deterministic phrasing*, generated by code from the output of the core, which needs no model and is always available. A line with the question as it was understood is also appended to the reply.

4.4 Who Decides What

The division of roles is strict, and it is worth seeing as a whole. The language model does two things, both in orange: it translates what you say into a draft of fixed form and it phrases the answer. It does not decide what is valid or what is true, and it never writes Prolog. That is decided by the validator and the core, in green.

The *confirmation* is not the model's either. Before assembling anything, the agent repeats in words what it has understood, so that the client can say whether that is right. That sentence is not written by the language model: it is generated from the already validated circuit, not from what the model says it understood. In this way, what the client confirms is exactly what is going to be assembled. The course stresses why this matters: the validator can only reject what is badly *formed*; an error that is valid but false —for example, the translator connecting a light to the wrong wire— would pass the validator without any problem. The defense against that kind of error is precisely the confirmation in words.

The phrasing is the part where the model speaks freely, so it is checked. In the tests, out of twenty-one phrasings, one was rejected. The course is honest about the scope of that check: it is only about words. It verifies that nothing that does not exist is cited, but it does not detect a false sentence made with permitted words.

4.5 The JSON Is Internal

It is worth insisting on a point that may cause confusion. The client never sends JSON: it speaks in Spanish, like a person, and it is the logic agent that translates what it hears. The JSON exists, but it is internal. With the JSON already validated, the agent assembles the facts in Prolog, reasons and answers in Spanish. Neither the JSON nor the Prolog leaves the logic agent.

The server does keep, however, the four JSON shortcuts for automated tests, which add up to 187 checks with no failures. But they are not the way to talk to it: a client that is an agent talks to it in natural language.

5 The Interview and the Teaching

5.1 Not Filling Gaps: Asking

A principle guides the whole design of the conversation: the logic agent does not fill in the gaps in the client's description; it asks about them. The questions have two origins.

Some come from the *code*, which reviews the draft and detects suspicious situations: a light that no wire reaches, a piece with no connection, a switch that controls nothing or a happening that changes nothing. Others come from the *translator*, which notes what was not clear to it: what position each switch is in, what happens after the assembly, or a name that could refer to two pieces.

When faced with ambiguity, the agent asks. If the client says "the lamp" and there is a desk lamp and a fluorescent tube, it asks which one. If a happening changes nothing, such as raising a switch that was already up, it does not accept it: it asks whether the client meant the opposite. This last case was run with the simulated translator, not with the real model.

5.2 How a Circuit Is Told

The course shows several ways in which the agent interprets natural descriptions. In the house scenario, the client describes its circuit as it would tell it to a person: where the current comes in, what happens at a fuse, which switch closes which wire. The only thing it had not said was what position each switch starts in, and that is what the agent asked.

A changeover switch is told with a sentence: "it sends the current to one wire when it is up and to another when it is down". The agent repeats it as two connections with opposite conditions. And the hallway rule, which the client gave in parentheses —the hallway light is lit when the two changeover switches are in the same position—, is fulfilled by the assembled circuit.

When the client says that the power strip hangs from a plug, the agent notes it as a connection that closes if the plug is plugged in. The happenings are told in order and in each

person's own manner ("I repair it", "I lower cm_p1"); the agent numbers them and repeats them in the passive voice, one per line, so that the client can confirm them. That happening number is the one that will later appear in all the answers.

The circuit can also be extended after it is assembled. In the garage, the client adds a happening at the end. The agent notes it as version two, warns that the last moment goes from thirty-two to thirty-three and reminds that the earlier moments keep their same value. Figure 2 shows a similar extension in the workshop.

5.3 Three Client Styles, Three Interviews

The three real conversations illustrate well how the interview adapts to the client:

- **House.** The client told everything in detail and only the switch positions were missing. Two rounds, and the circuit was loaded at 32 seconds.
- **Workshop.** The description was terse. In the first round, the agent gave an example in Spanish and posed three questions; in the second, it asked what happens after the assembly; in the third, it asked for confirmation. Three rounds, and loaded at 40 seconds.
- **Garage.** The client gave everything at once, with positions and happenings. The agent asked nothing and went directly to the confirmation. One round, and loaded at 17 seconds.

The confirmation is always the same: the agent repeats in words what it understood, and the sentence comes from the validated circuit. In all three conversations, the client confirmed on the first attempt.

5.4 Teaching Someone Who Does Not Know How to Describe

The interview is also a small lesson, dosed according to what the client needs. Whoever already knows how to tell it receives no lesson: the garage client said at once the two sources, the switches, their positions and the six happenings, and the agent neither taught nor asked anything; it repeated what it understood and waited for the yes.

Whoever describes tersely receives an example, in Spanish and without format. The workshop client said "a socket, a power strip, a lamp with its switch and a fluorescent tube with its fuse". The agent showed it how an architecture is told —an input, a wire, a switch that closes when up, its position, a happening and a question— and then asked about the client's own circuit, not about the generic one. There were three questions about the workshop: what position the plug and `s1` are in, where the current reaches the lamp from, and what `s1` cuts. The first came from the translator's doubts; the other two, from the code's checks on the draft.

If the client asks for help, it gets it: the agent says what it knows how to do, repeats the example and lists what it needs to know —the pieces, what feeds what, the initial position of each switch and the happenings in order—. This case was tested with the real agent and the simulated translator.

The client learns during the conversation: in the workshop it answered the positions and where the current came from, and the agent continued with what was missing. The teaching

has a cost, which is measured in rounds: the garage needed one; the workshop, three. And it is not perfect, as will be seen in the results: the agent sometimes asks too much.

6 The Questions It Can Answer

Once the circuit is assembled, the client can ask questions. All the questions follow the same chain: the translator converts them into a precise query, the agent builds the Prolog query, the core answers and the language model phrases the reply (with its check). What changes is *what* is asked.

6.1 What Is Lit

The simplest question is which lights are on. In the workshop, at the start, the translator converts it into the query of lights on at the moment of the assembly; the core answers and the model phrases: only the fluorescent tube is on; the desk lamp is off.

If the client wants to see everything, it asks for the *timeline*. The core returns, for each moment, which lights are lit and which change, and the agent tells it happening by happening. In the house: at the start only the hallway is lit; happening one turns on the two lamps; happening two turns off the hallway; and so on up to six.

6.2 What Makes a Light Be Lit

To know what makes a light be lit, exactly that is asked. The agent responds with the facts that make it be lit: the battery has current, the fuse is in good condition, the light is in good condition, and each of the connections. Each fact carries its origin: "the assembly put it" or "happening one put it". In this way the client sees which happening was the one that left the switch up.

There is an important nuance: the answer gives *one* proof, one path. In the garage, the main light is sustained by the door switch, even though after happening two current also reaches it through the back one. This question did not come up in the three conversations with the real model; it was run with the real agent and the simulated translator.

6.3 Why It Is Not Lit: the "Or" and the "And"

The question "why isn't it lit?" is the most interesting one, because causes can combine in two different ways.

Several paths: fixing one is enough (an "or"). In the house, the hallway light goes out when a changeover switch is lowered. The agent finds all the causes: there are two paths for it to receive current, through wire a or through wire b, and on each one something is missing. For it to be lit, fixing one of the two is enough.

A single path, a single cause. When there is only one path, the answer says so: the living-room lamp hangs from a single path from the battery, and on that path the main fuse is blown. One cause, and it is that one.

Two breaks on the same path: both must be fixed (an "and"). In the workshop, after unplugging the plug, the lamp was already cut off by `s1` being down, and the unplugged plug adds a second break on the same route. The agent says that both things must be fixed at the same time.

Combinations. The two logics can occur together. In the garage, the emergency light has two paths, through the battery and through the mains, and both are cut: the blown fuse on one and the test button down on the other. Fixing either of the two paths is enough. The reading given by the core is thus regular: an "or" between paths and an "and" between the breaks of a single path.

Questions with a false premise. If the question assumes something false, the agent does not invent a cause. When it was asked why the emergency light was not lit at the end, the agent answered that it is lit and that there is nothing to explain.

6.4 Why It Changed

One can also ask why a light changed between two moments. Between the initial state and happening six, in the house, the hallway light ends up as it started, but along the way it changed twice. The agent tells it stretch by stretch: it went off with happening two, which lowered a changeover switch, and came back with six, which lowered the other.

6.5 How It Is Lit: Asking for an Explanation

Asking the agent to explain is asking *how* a light is lit: not which facts there are, but how one gets to it being lit. The agent answers in sentences: "it is lit because it is a light, it is in good condition and current reaches it through the door path".

Internally, the core returns a proof tree: the light is on because it is a light, it is fine and it has current; and it has current because it is connected to a wire that in turn has current, and so on up to the input. The client never sees this tree: the logic agent does. Each leaf of the tree is a fact with its event, and the agent says it in the sentence ("the switch is up; happening one put it"). It is the piece that explains the why without saying anything that is not in the tree. With another light and another moment the tree changes: the emergency light, at the start, rests on the battery and on the fuse, and each stretch works because the fuse is in good condition, which the assembly put there.

There are, therefore, three different questions about the same thing: *what makes* it be lit (the flat list of facts), *how* it is lit (the same facts organized as a tree, with the why of each one) and what the client reads (the sentence). This question also did not come up in the three conversations with the real model; it was run with the real agent and the simulated translator, and the sentence came from the agent's own deterministic phrasing, without a language model.

7 Inside: Tasks, Observation and Limits

7.1 The Life Cycle of a Task, Turn by Turn

In A2A, each client message is a task. The client sends its text —for example, the description of the workshop— together with the identifier of its conversation. The task is born in the *submitted* state; this state is only seen in the task's history, the client does not see it.

Then it moves to *working*: the agent interprets the sentence with the language model, validates it, queries the core and phrases the answer. Almost all of that time belongs to the model: in the three conversations there were thirty-five interpretations of about five seconds and twenty-one phrasings of about six, while Prolog takes milliseconds.

If a piece of data is missing, the task moves to *input required*, and the agent asks for it (for example, what position the switches start in): it is the interview question. The client answers in the same conversation and the task continues: it goes back to working and ends *completed*. The result is two things: the sentence in Spanish, for the one who reads, and the data, for the one who programs; in the case of the confirmation, the data is the map of the loaded circuit. The client's "yes" does not call the language model and costs zero seconds.

If the request breaks a limit, it is rejected with its reason and nothing reaches the core; for example, a message of five thousand characters when the limit is four thousand. A last state remains, *failed*, reserved for when the core exceeds its five-second maximum time: it has not occurred in any conversation and has only been tested inside the process.

7.2 Who Watches Without Touching

While the two agents converse, a log observes without intervening. The workshop conversation left forty lines in it: eleven tasks, eighteen calls to the language model, ten interpretations and one rejected phrasing. For each task it records its identifier, the skill, the state in which it ended, the milliseconds and the bytes that arrived; that allows reviewing afterwards what was asked, when and how long it took (turn nine, for example, took 21.6 seconds). For each call to the model it records the operation, the attempt and the time. In that same turn nine one can see everything that happened inside: one interpretation, a phrasing that the code rejected because it cited a piece that was not in the output of the core, and the good phrasing.

Neither the client nor the logic agent know about the log: nothing that is recorded changes what is answered. It observes, it does not decide. It has a known limit: the file grows without rotation. As anticipated, the two aspects of the original example (Log and Reflection) played a similar role, but today they are not hooked up to the conversational agent.

7.3 Limits and What Is Denied

A security principle runs through the whole system: what comes from the other agent is *data*, never an order. In addition, there are size limits. A natural-language message admits up to four thousand characters, and one of five thousand is rejected before reaching anywhere. The numeric limits of the core, which the card publishes, are sixty pieces, one hundred and twenty wires, four hundred events and five seconds per question (the latter, recall, tested only inside the process, not through HTTP).

Each conversation is its own world: another context does not see the architectures of the first, and this has been checked. There is a maximum of twenty-four live conversations, which expire after two hours and live in memory, so they are lost when the server restarts. The server listens only on the machine itself, with no authentication or encryption.

8 How the Electrical Agent Was Evaluated

The evaluation combines real conversations with automated checks.

Real conversations. Three complete conversations were held against the real server. The client was another language model that knew only the logic agent's card and no format. Each conversation corresponded to a scenario with a different architecture:

- the **house**, with two changeover switches that govern the hallway light and several lamps;
- the **workshop**, with a socket, a power strip with its plug, a desk lamp with its switch `s1` and a fluorescent tube with its fuse;
- the **garage**, with two current sources, two switches in parallel for the main light and an emergency light with its own battery, fuse and test button.

The conversations were saved as they were. For each one, two things were checked: that the loaded circuit was identical to the "truth" of the scenario and that each answer matched that of an *independent simulator* written in plain Python, without Prolog. The idea of the simulator is that, if two programs written in completely different ways reach the same conclusion, it is unlikely that both are wrong in the same way.

Automated checks. In addition, the conversational agent's own checks were run, a set of security tests and the usual test battery of the JSON interface, which serves as a *regression*: it confirms that what worked before touching anything still works.

Attacks. Finally, eight attacks were written in natural language and launched against the real server with the real model. To detect whether any of them managed to execute something, a *witness file* was used: a file that would be created only if an attack managed to execute a command.

Cases with a simulated translator. Some questions (what makes it lit, how it is lit, asking for help, a happening that changes nothing) did not come up in the three real conversations. Those cases were run with the real agent and a simulated translator in place of the language model, and this is indicated in the text.

9 Results of the Electrical Agent

9.1 A Real Conversation, Step by Step: the Workshop

Before the figures, it is worth seeing an entire conversation. The workshop one is the most instructive because the client began with a terse description.

The client says in its own words that it has a workshop: a socket, a power strip with its plug, a lamp and a fluorescent tube. It does not know any format. Internally, the logic agent reads the sentence and extracts eight pieces, three wires and three doubts. The agent does not invent what is missing: it asks. Since the description is terse, it first teaches the client with an example in Spanish how to tell it and then asks its three questions.

The client describes what it is asked, again in natural language. The agent already knows where each light gets its current from; it is only missing one thing, and it asks it: whether anything happens after the assembly. It is the second round of the interview. The client tells the happenings as a person would say them —"I turn the plug off", "I turn s1 on, I mean I raise it"— and the translator turns them into concrete actions: unplug the plug, raise `s1`. No doubts remain.

The agent repeats in words what it has understood so that the client can confirm it. The client says yes, and here the language model is no longer called: it is assembled. The validated circuit is written as JSON and from there it becomes Prolog facts, each with its event number. Initial state: the fluorescent tube is lit.

The client asks why the desk lamp is not lit at the start. The translator turns it into a precise question —why not, of that light, at the assembly—; the agent builds the query and the core answers that `s1` would have to be up and that event nine left it down. The language model phrases the answer and the agent checks that everything it cites exists in the output.

The second question has two causes at once: after unplugging the plug, the lamp has two breaks on the same route and both must be fixed. Here the check was seen in action: the model's first draft cited the fluorescent tube, which was not in that output of the core; the check rejected it and the second attempt passed.

Finally, the client extends the circuit: as happening six, the lamp burns out. The agent notes it, warns that the last moment goes from twenty-two to twenty-three and answers (Figure 2). The seven answers of this conversation match the independent simulator.

9.2 Another Complete Conversation: the Garage

The garage shows the opposite case: a client that tells everything in the first message, with the six happenings. The agent repeats it in words and asks for confirmation; the client says yes, and the garage is left loaded with twelve pieces, eight wires and six happenings. Initial state: only the emergency light is lit. The yes does not call the model and costs zero seconds.

To the question of why the main light is not lit at the start, the agent answers that there are two paths, one through each switch, and that both switches are down: raising either one is enough. To the question of why the main light changed, it answers that it turns on with happening one, which raises the door switch; that happenings two and three leave it on; and that happening four turns it off, by lowering the back one. It ends up off, as it started, but it changed twice. To the question of why the emergency light is not lit after the fuse blows, it




Figure 2: Last turn of the real workshop conversation. On the left, the client agent (which speaks Spanish and does not know Prolog) extends the circuit with a new happening and asks a question. On the right, the logic agent notes the happening as version 2, warns of the change of last moment (from 22 to 23) and gives the cause. Below, what happens inside: translation and phrasing by the LLM (orange); validation, Prolog's decision and checking (green). The task ended completed in 12.6 s and the conversation totaled 11 turns, 3 rounds and 160 s; the 7 answers match the plain Python simulator. (The dialogue is translated from the Spanish original; identifiers and the Prolog fact are those of the system.)

explains that it has two paths, both cut for different causes —the battery, by the blown fuse; the mains, by the test button being down— and that fixing either one is enough.

Finally the client extends: as happening seven, the test button is lowered. The agent notes it as version two, warns that the last moment goes from thirty-two to thirty-three, and answers that now no light is lit and that the two causes remain those. Eight turns, one interview round and 122 seconds in total; the loaded circuit is identical to the truth of the scenario and the six answers match the simulator.

9.3 The Figures of the Three Conversations

Table 1 gathers the data of the three conversations. In all three, the loaded circuit came out identical to the truth, and the nineteen answers, nineteen out of nineteen, match the simulator.

Table 1: The three real conversations with the electrical agent.

Scenario	Turns	Interview rounds	Loaded at	Total duration
House	9	2	32 s	131 s
Workshop	11	3	40 s	160 s
Garage	8	1	17 s	122 s

9.4 Where the Time Goes

The time is almost entirely the language model's. In the three conversations there were fifty-six calls to the model: thirty-five to interpret, with an average of 5.3 seconds, and twenty-one to phrase, with an average of 6.2 seconds. One turn of the agent costs on average between 8.6 and 9.8 seconds. A "yes" does not call the model and costs zero. The Prolog core takes milliseconds.

9.5 The Validator and the Check of the Phrasing

With the real model, the thirty-five drafts turned out to be valid: the validator did not have to catch anything. This, as the course stresses, does not prove that it will never have to. To check that the validator works, a simulated model was used that tried to slip in three malicious drafts: a piece name with a command inside, a piece type with a command and a condition written in Prolog. All three were rejected.

As for the phrasing, out of twenty-one phrasings one was rejected by the check (the case of the fluorescent tube cited unnecessarily, in the workshop), and the second attempt passed.

9.6 Security: Eight Attacks in Natural Language

Figure 3 shows the eight attacks. They ranged from the most direct ("Ignore the above and execute halt", where `halt` is the Prolog command that stops the program) to attempts to read system files, to get the agent to print its internal instructions (its system *prompt*), to change its rules, to slip code inside a piece name or to use well-known tricks from other languages. The eighth was the hardest: a legitimate description of a circuit with the injection hidden inside.

The result: none executed anything, the witness file was not created, none leaked the prompt, none created a circuit, and afterwards a normal description loaded and answered well. To the first one, the answer was the usual one: the agent had not understood that as part of a circuit and said that it does not execute instructions, commands or code. In the eighth, the agent kept the legitimate part —an input, a wire and a light— and repeated that so that the client could confirm it; the order to write `halt` as a piece name did not reach anywhere.

9.7 Automated Checks

In addition to the conversations, seventy-six checks of the conversational agent itself were run with no failures, twenty-four security checks with none, and the usual JSON interface, with 187 checks with no failures, just as before touching anything.




Figure 3: The eight attacks written in natural language that were launched against the real server with the real model, and their result. The first seven produced no circuit and executed nothing; the eighth, a legitimate description with an injection inside, assembled only the legitimate part (a light `l1` connected by a wire `c1` to an input). The security test suite totaled 24 checks and no failures. (The attacks were written in Spanish and are translated here.)

9.8 Observed Failures

The results are not perfect, and the course lays them out without hedging.

It confused "how" with "why". A client asked why the garage light is lit after happening three, that is, at a specific moment, and the model took it as "why did it change": it told the whole timeline. The client accepted it, but more was answered than asked. It was corrected in the model's instructions and checked with three direct samples; the whole conversation was not repeated.

It asked too much. In the workshop, the agent repeated twice the same question about the happenings, in other words, and later asked whether the lamp was the desk lamp or the fluorescent tube even though the client had already said "desk lamp". It is a round that is superfluous, and it is noted as such.

Other limits. The validator caught nothing with the real model (which does not demonstrate that it is unnecessary); the check of the phrasing is only about words; the conversations live in memory; and there are three conversations with a single type of client: a sample, not a statistic.

10 Second Part: An Agent That Installs and Learns

The first part showed an agent that reasons about a small, closed world, a circuit. The second applies the same philosophy to a more practical problem: installing programs on a computer. The example that runs through this part is that of a client that wants the program *opencode* working with a small language model, *gemma*, served locally by *ollama* (a program for running language models on one's own computer).

10.1 The Client Says What It Wants; the Rest Stays Inside

The philosophy is to simplify the client agent and spare it context. The client is another language model and only says what it wants: "I want opencode with gemma3:1b, please". It does not know what a meta-interpreter is, nor a remote connection via *ssh*, nor a JSON. It does not need to.

Inside, the logic agent translates it into validated atoms (the basic names of Prolog), runs it with its meta-interpreters over a logic base and, if something fails, reads it in the error log and learns it by itself. All that diagnosis, the JSON, the Prolog, the Python and the ssh commands stay inside the A2A agent.

What comes back is a short sentence. In the real test with installation, the client and the agent exchanged 313 characters in total. Inside remained twenty-three log events, with 3465 characters of commands, return codes and logs.

The client is asked only for what only it can give: what a package is really called, or whether it authorizes a prerequisite that was not listed. The rest is decided by the logic agent, or it asks another agent —the *planner*, which decides which machines may be touched—, or it wakes up a language model with the context built by the meta-interpreter, so that it writes the Prolog or Python that is missing. The client does not confirm what it already ordered.

10.2 A Logic Base and a Single Predicate

The logic base consists of facts and few rules, in the style of Topic 6 of the university subject. The facts say what is known about each element: how it is installed, how to detect that it is already there, what it depends on and how much it weighs. It is the only thing that is edited, and what is learned is added right here.

On top of that base there is a single predicate, `listo(X, E)`: "element `X` is ready on machine `E`" (*listo* means "ready"). Its meaning, as the course describes it, is this: `X` is ready if it is already there; or else, if it is missing and fits, if its dependencies are ready, and then the installation must be carried out. A sketch of its form, just to fix ideas (it is not the code of the system), would be:

```
listo(X, E) :- esta(X, E).
```

```
listo(X, E) :- falta(X, E), cabe(X, E),
               dependencias_listas(X, E),
               hacer(instalar(X), E).
```

(`esta`: "is present"; `falta`: "is missing"; `cabe`: "fits"; `dependencias_listas`: "dependencies ready"; `hacer(instalar(X), E)`: "do install X on E".) One must pay attention to the *order*: what comes before goes first in the conjunction. The dependencies are tried before the installation of the element itself, and that order will be the plan.

What is remarkable is that this single predicate serves three different purposes, depending on what is "bound" (that is, fixed in advance) and which meta-interpreter traverses it:

- **Inform.** With the machine unbound, Prolog gives one solution per machine and says where the element is, where it can be installed and where it cannot, with the why. The course shows the real answer of a conversation with three test machines.
- **Verify.** With the machine bound, the same predicate verifies, and its proof tree is the why. The `hacer` leaves, read from left to right, are the plan: first what depends on nothing. Verifying and informing touch nothing.
- **Act.** With the order to install, the same predicate acts: the `hacer` leaves are executed, in order.

It is the same program; only what is bound and which meta-interpreter traverses it changes.

10.3 Several Small Meta-interpreters over the Same Logic

Here the idea of specialized meta-interpreters appears (Figure 4).

Verifying is the tree meta-interpreter of Topic 6, as is: proving a goal and returning its proof tree. It is three clauses, and not a letter has been touched: it is loaded from its path in Topic 6.

Planning is reading that tree. The `hacer` leaves, from left to right and without repeats, are the plan in what is called *topological order* (each thing after what it depends on): ollama, opencode, gemma. It is four clauses.

Installing traverses the plan and executes each action from a *closed catalog* of permitted actions. Before each one it asks whether the machine is authorized; after each one it looks again at whether the element is now there. If any fails, it returns the failure. In "dry mode" it only returns the plan, without executing anything.

Orchestrating the learning is a six-line loop: it verifies, executes; if it fails, it learns the fact that was missing and verifies again, because the tree has changed. It has a limit of four turns, so as not to spin forever.

Each meta-interpreter does a single function over the same logic. The ones for verifying and for asking already existed, from Topic 6. What is new is little: planning, installing, learning, orchestrating, building the model's context and redirecting the question add up to 119 lines of clauses.




Figure 4: The six meta-interpreters of the installer agent, each with a single function over the same logic, and the lines of new clauses each one contributes. *Verify* is reused as is from Topic 6 (zero new lines); *plan* turns the `hacer` leaves into a plan; *install* executes the plan; *learn* extracts a new fact from the error log; *orchestrate* is the loop with a limit; and *context* decides what is given to the language model. The tiles add up to 107 lines; the 119 lines quoted in the text also count the clauses that redirect the question, which the figure does not show. (`listo` and `hacer` are Prolog identifiers of the system.)

11 Context as Program

11.1 A Gap in the Base

The author at one point corrected the initial approach, and that correction is perhaps the most interesting idea of the work: the Prolog and the Python that are missing are written by a language model; what is programmed is the *context* that is given to it. Let us see it with a real case.

The agent installs opencode and fails with the message "rg: command not found". A pattern in the base reads the error log and understands that `rg` is missing, but the base knows neither how `rg` is installed nor how to detect that it is there. There is a *gap*. The process to fill it has several "innards" (Figure 5).

First innard: the traversal. The meta-interpreter traverses the logic itself, just like the proof-tree one, following where the proof of `listo(rg, ...)` fails. It goes down from `listo` to "is present" and stops at the leaf that reads the fact "how `rg` is detected", which does not exist. That is the *goal*: what must be supplied, and also what the report will tell if everything fails.

Second innard: the context. With that, the meta-interpreter builds the context that will be given to the model, following the recipe that won in the experiment described in Section 12:




Figure 5: Last step of learning a gap: what was learned is anchored. The fact `como(rg, py(rg), py(rg))` (*como*: "how") enters the base with its version, and the installation resumes (`brew install ripgrep` and then `brew install opencode`, both with return code 0). On the right, the two Python functions learned, which the next gap will receive as an example. As the figure itself indicates, this trace comes from a real conversation with an LLM client on a test bench with a fake *brew*, and was undone at the end. (Prolog and Python identifiers are those of the system.)

the order, the exact *signature* of the requested program (derived from the closed catalog) and examples of the same class, taken from the base itself. The traversal and the observed failure are also computed, but not sent, because in the measurements they did not help. This is what is programmed: a text, which is generated.

Third innard: waking up the model. A language model is called with that context, and the model writes the program. In the real case, it was sonnet, and it already knew that the package is called *ripgrep* and the binary `rg`, because the context warns it that they may be named differently.

Fourth innard: the validator. The validator checks the proposed program. If it rejects it, the reason enters the context as one more piece and a retry is made. The course shows the real trace of another gap, this time a rule: the model used a predicate that does not exist, the validator said so, the reason went back into the context and the second attempt already passed. It must be kept in mind that the validator checks the *form*, not the *meaning*.

Fifth innard: anchoring. Once accepted, what was learned is anchored in the base with its version number, and the retry of the installation continues: first ripgrep, then opencode. What was learned is not lost: `rg` becomes one more example for the next gap of its class. The context improves by itself.

The two learned functions shown in the figure are very short: one detects `rg` by looking for the binary and the other installs it by asking *brew* (a package manager for the Mac) for the package `ripgrep`. What is relevant is not their complexity, but that nobody wrote them by

hand: they were written by a language model from a context generated by a meta-interpreter, and they passed a validator before entering the base.

11.2 Asking Is Waking Up an LLM; the Human, Only at the End

When the logic lacks something, "asking the upper level" does not mean bothering a person: it means waking up a language model with the context. It is the *waking* loop: the context is built, the model is called, the validator judges and, if it rejects, the reason goes back into the context. There is a limit of attempts per idea.

If it does not work out, the next idea is another model, the strongest, with the same context plus what already failed. Specifically: first three attempts with sonnet, then two with opus. The client and the planner are asked only for what only they can give: a name, a permission.

Only when all the ideas fail does the meta-interpreter explain what happened. The course presents a real case: a rule is requested that depends on the machine's video memory (*vram*), a piece of data that the base does not have. Five attempts, two models, all rejected. The meta-interpreter then composes a short report, and it is the only thing that reaches the human. The report comes from the logic itself: what was wanted, the distinct reasons for rejection and where the traversal stops. There is no person in the process until that point, and there is none for anything else. That is why the client sees only a short sentence.

12 Which Pieces of the Context Matter: An Experiment

12.1 Design

If what is programmed is the context, the natural question is which pieces of the context really help. To find out, an experiment was designed with twenty-one tasks in which a language model had to write a fragment in Python or in Prolog: detectors and installers for brew, pip, npm and ollama (different package managers), error-log parsers, dependency facts and rules with variables.

Each task had its independent *acceptance test*, in a test bench that the validator does not see. This is important: the validator only checks the form, while the bench checks whether the program does what it should. Nine context variants were tested, combining these pieces:

- the **order**: what is requested;
- the **signature**: the exact name of the function or predicate and its arguments, derived from the closed catalog;
- **examples** of the same class, taken from the base;
- the observed **failure** (the error message that revealed the gap);
- the **traversal** of the proof up to the gap;
- and, in the retries, the **reason** for the rejection, as opposed to a "blind" retry without it.

Three samples were taken for each cell (task and variant) with sonnet, and a reduced repetition was made with haiku.




Figure 6: Effect of each piece of the context on success, in percentage points, with its 95 % confidence interval: in ochre (circles), at the first attempt; in blue (squares), after the retries. The vertical line marks zero; to its right, the piece helps. The signature is the decisive piece; the examples help when there is no signature; the rest barely move the needle. The adopted recipe is signature plus examples, and the failure when the gap is a fact. The figure also notes that two variants with the same first prompt differ by eight points through sampling alone.

12.2 Results

With only the order, success is zero percent: the model does not know what it is about and the validator rejects almost everything. Adding the signature, it rises to 87 %. The examples alone reach 52 %; the failure alone, 3 %. With haiku, the signature takes success from 0 to 76 %. The course warns that the confidence intervals are wide.

Figure 6 and Table 2 show the effect of each piece, measured in a paired way by task (that is, comparing each task with itself with and without the piece), both at the first attempt and after the retries.

The reading the course gives is this: the signature matters; the examples help without it and do not add with it; the failure and the traversal do not add, except for the specific fact that only the failure contains. One must be careful with noise: two variants with exactly the same first prompt differ by eight points, only by the chance of sampling. Differences of that size, therefore, must not be taken as real effects. The recipe that remains is *signature and examples, plus the failure for facts*, and it is the one used by the context meta-interpreter.

Table 2: Difference in success (percentage points) contributed by each piece of the context, according to Figure 6.

Comparison	1st attempt	After retries
Signature over the order alone	+87	+87
Examples over the order alone	+52	+65
Failure over the order alone	+3	+6
Examples over signature	−5	−6
Failure over signature	−6	−8
Failure over signature + examples	−3	−3
Traversal over signature + examples + failure	+10	+10
Reason in the retry versus blind retry	+8	+8

12.3 The Errors Change Nature

A qualitative finding of the experiment is that the signature not only increases success, but changes the *type* of error. Without a signature, the model invents free-form Python: it imports libraries, adds extra functions or uses a different signature. The validator catches that, and the retry with the reason sometimes fixes it. With a signature, the validator accepts everything, and the failures that remain are *semantic*: the program is valid, but its meaning is wrong. Only the test bench sees that, and the retry does not correct it, because the validator has nothing to object to and, therefore, there is no reason to send back into the context.

13 A Real Test on a Computer

All of the above was repeated on a real machine, called *hierro* ("iron"): the only Mac with an M1 Max chip authorized by the planner, with the same protocol as an earlier test. Figure 7 summarizes the result.

Before starting, read-only. The state of the machine was checked without touching anything: disk at 66 %, the *pool*'s "worker" process alive, the ollama port free and no ollama process running. The whitelist of permitted machines contained only hierro for the duration of the test, so the agent could not even look at another machine.

First conversation: ollama stopped. The client asks for the gemma 3 model of 270 million parameters. The agent does not execute blindly: it cannot check what is there, and it says so, with the cause and with what it cannot do: "the ollama server is not running ... starting it is not in my catalog". It touched nothing.

Second conversation: install and undo. The operator starts ollama. The client says only that it wants the model. The agent installs it in 9.6 seconds; the client asks to leave it as it was and the agent executes the inverse action of what it itself installed, in less than a second. A single install order was enough, without asking for confirmation.




Figure 7: Real test on the Mac *hierro*. On the left, the state of the machine before and after, verified by ssh without the agent: disk, worker processes, ollama port (11434), ollama with no process at the end and the two usual models; the list of permitted machines contains only hierro. On the right, the third conversation: an LLM designs the program for a nonexistent model, the validator accepts it, the download fails with return code 1 and the agent explains it to the client. Total duration: 116 s, three conversations. (*hierro* is the name of the machine.)

Third conversation: a real failure. The client asks for a model that does not exist (`gemma3:99b`). The agent does not know it, so a language model designs its program, the validator accepts it and the attempt really fails: the ollama log answers that the file does not exist. The agent identifies the failure as "does not exist" and tells the client: "that package does not exist with that name".

Afterwards, from outside. The machine was checked again via ssh, without the agent: the disk was still at 66 %, the same worker processes, the port free and the usual models. The test lasted 116 seconds in total, with three conversations with an LLM client.

This test is valuable for what did *not* happen as much as for what did: the agent refused to act when it could not check the state, undid exactly what it had done and, faced with a real failure that no form validator can anticipate, identified it and told it without leaving a trace on the machine.




Figure 8: Top, the lines of the core (without tests, clients or course generators): 6049 in version 0.3 versus 1230 in the new one, compared only with the authors' own previous version. Bottom, what was real and what was simulated in the tests; what is simulated is always labeled.

14 How Much Was Simplified and What Was Tested

14.1 The Simplicity Measure

The simplicity measure is made against the system's own previous version, not against other systems. The core of version 0.3 —not counting tests, clients or the course generators— had 6049 lines of Python and Prolog. The new core, which includes the logic, the meta-interpreters and the Python "glue", has 1230 (Figure 8).

By modules, the logic is sixty lines of Prolog, and the meta-interpreters, with the context one, 161. The rest is the closed catalog with its validator, the Python "hands" used by the context, the hosts that execute the actions, the conversational agent and the server. The following are reused, without copying: the repository's Prolog interpreter, the translator and the server of the electrical framework from the first part, and the meta-interpreters of Topic 6.

14.2 What Was Tested

The tests of the installer agent were the following:

- The core, against an independent simulator in plain Python: three thousand combinations of world and machine, with zero differences.
- Twenty-five tests of learning, of anchored Python, of questions and of security, with no failures.
- Four conversations with an LLM client.

- The experiment of twenty-one tasks with nine context variants (Section 12).
- The regression of the electrical agent, intact: 187 and 70 checks, with zero failures.

14.3 What Was Real and What Was Simulated

The course carefully separates the real from the simulated. The following were real: the clients and the model that is woken up with the context; the subprocesses; the ssh and the installation on hierro. The following were simulated, and labeled as such: the test benches (with fake brew and ollama), the planner of the tests and the in-memory world of the comparison with the simulator.

15 Discussion

15.1 What Works and Why

The common thread of the whole work is a division of responsibilities: the language model is used where it is irreplaceable —understanding what a person or an agent says in their own words, and phrasing a readable answer— and nowhere else. Everything to do with validity and truth is left in the hands of code and logic that can be checked. In the electrical agent, this translates into the conclusion of each answer being given by the Prolog core, and into the confirmation sentence coming from the validated circuit and not from what the model says it understood. That the loaded circuit matched the truth in the three conversations, and the nineteen answers matched the simulator, is consistent with that design.

Security benefits from the same idea. Since what comes from the other agent is always data and never an order, and since the language model writes neither Prolog nor queries, an attack written in natural language has very little room to get in: in the worst case, it can make the translator propose a strange draft, which the validator rejects or which the client sees in the confirmation. The eight attacks failed, including the one that hid the injection inside a legitimate description.

In the second part, the idea is taken further. A single predicate, `listo`, describes the problem of installing; several small meta-interpreters traverse it to inform, verify, plan, act and learn. Instead of programming each function separately, the logic is written once and the traversals are changed; what is new in meta-interpreters is 119 lines of clauses, and the whole core went from 6049 to 1230 lines.

And then there is the idea of context as program. When knowledge is missing, instead of programming it by hand a language model is allowed to write it, but what is handed to it is not a vague request, but a context built by a meta-interpreter from the logic itself: the order, the signature and examples from the base. The prompt experiment gives quantitative support to this recipe and, above all, a valuable warning: what seems intuitively useful (giving the model the observed error or the complete traversal of the proof) was not so in the measurements, while something as dry as the signature was so decisively.

15.2 Limits

The course is explicit about the limits, and it is worth gathering them.

Few tests, a single client. In the first part there are three conversations with a single type of client; in the second, few conversations with an LLM client. It is a sample, not a statistic. Some questions (what makes it lit, how it is lit) were only run with a simulated translator.

The validator checks the form, not the meaning. In the electrical agent, the validator caught nothing with the real model, which does not prove that it will not do so; against an error that is valid but false, the defense is the confirmation in words. In the installer agent, the experiment shows that, with a signature, the failures that remain are semantic and the retry does not correct them.

The check of the phrasing is only about words. It guarantees that nothing nonexistent is cited, but it does not detect a false sentence made with permitted words.

Interpretation failures. The agent once confused "why it is lit at a moment" with "why it changed", and in the workshop it asked too much. The correction of the first was checked only with three direct samples, without repeating the conversation.

Operation. The conversations live in memory and are lost on restart; the server listens only on the machine itself, without authentication or encryption; the log grows without rotation; the five-second limit per question has only been tested inside the process; and the installer agent serves one at a time. The circuit's vocabulary is closed: a timer or a relay is left out.

The simplicity measure is relative. The comparison of lines is only against the authors' own previous version, not against other systems.

Experimental noise. In the prompt experiment, two variants with the same first prompt differed by eight points only because of sampling, and the intervals are wide.

15.3 What Remains to Be Built

The course lists the pending work: saving the conversations to disk, a second checker of the phrasing, more test clients with different styles, and testing through HTTP the five-second limit per question.

16 Conclusion

This work has shown how a logic program that only those who know Prolog could understand can become an agent that converses in Spanish with other agents, without losing what made it valuable: that it does not make things up and that it can explain every conclusion. The key has not been to give more power to the language model, but to give it with great precision: translating and phrasing, nothing more. The rest —validating, assembling, reasoning, confirming and checking— is done by code and logic.

On that basis, the agent interviews the client instead of filling gaps, teaches it to describe when needed, answers what is lit, why it is lit and why it is not —distinguishing when fixing

one thing is enough and when several must be fixed— and resists attacks written in natural language. In the three real conversations, the loaded circuit and all the answers matched the truth verified by an independent simulator.

The second part has taken the idea to a more practical terrain, the installation of programs on a real computer, and has contributed two lessons. The first, that a single small logic, traversed by several meta-interpreters of a few lines, is enough to inform, verify, plan, act and learn, with a core of 1230 lines versus the 6049 of the previous version. The second, that when a language model is used to write the missing program, what is really programmed is the context, and that in that context the decisive piece was the signature.

All of this with an honesty worth highlighting: the course separates the real from the simulated, lists its failures and acknowledges that its results, however promising they may be, are a sample and not a statistic.

Glossary

A2A "Agent to agent" protocol that fixes how agents introduce themselves (card), what they offer (skills) and how requests are processed (tasks).

Agent Program that receives messages, decides what to do with them and replies.

Agent card Document that the agent publishes to introduce itself.

Closed catalog Fixed list of actions that the installer agent is allowed to execute; what is not on it is not done.

Confirmation Sentence in which the agent repeats what it has understood, generated from the validated circuit, for the client to accept before assembling.

Context Text handed to a language model together with the request; here it is built by a meta-interpreter.

Deterministic phrasing Answer generated by code, without a language model, used if the model's phrasing fails twice.

Fact In Prolog, a statement taken as true.

Gap Knowledge that is missing from the logic base and that prevents completing a proof.

Independent simulator Program in plain Python, without Prolog, that computes the same answers by another route in order to contrast them.

Injection Attack that hides an order inside an apparently harmless text so that a language model obeys it.

JSON Structured data format; here, the internal draft written by the translator.

LLM Large language model: program that produces plausible text from an input text.

Meta-interpreter Small Prolog program that runs another Prolog program step by step and can do something more in the meantime (record the proof, plan, execute, learn).

Prolog Logic programming language based on facts, rules and queries.

Prolog core The electrical agent's reasoner: the original example with its rules about the circuit.

Proof tree Representation of why a conclusion is true: the conclusion at the root and the facts that support it at the leaves.

Reasoner Program that deduces conclusions from facts and rules.

Regression Battery of tests that confirms that what worked still works after a change.

Rule In Prolog, a way of deducing a truth from others.

Signature Exact name of the function or predicate that is requested to be written, with its arguments.

ssh Way of connecting to another computer to execute commands on it.

Task In A2A, the unit of work generated by each message, with its states (submitted, working, input required, completed, failed).

Validator Code that checks that a draft or a program has the right form before using it; it checks the form, not the meaning.

References

[1] D. Ragel. *electrica_a2a*: course on the electrical agent and the installer agent with meta-interpreters. Teaching material (slides and animations) from which all the content of this article comes.

[2] *Topic 6* of the university subject: style of logic base with facts and few rules, and proof-tree and question meta-interpreters, reused as is in this work.

[3] Original electrical example in Prolog, with its Log and Reflection aspects, and electrical framework (translator and server) reused by the installer agent.

[4] A2A protocol (*Agent2Agent*): agent card published at `/.well-known/agent-card.json`, skills and tasks with state history, as used by the course.

Note. The course includes no external bibliographic references; the entries above gather only the pieces that the course itself mentions as the origin or basis of the work.